


BLUESUN SOLAR CO.,LTD







Shingled Semi-Flexible Solar Panels

Warranty

- 2 years Manufacturer Warranty
- Warranty on Electrical Performance: 10 years 80% of power output

Manufacturing

- Original cell sorting system ensures the best electric cell match
- EL-Testing before packing.
- Comprehensive module power testing.

Performance

- Upgraded efficiency and unprecedented flexibility.
- Weakened hot-spot effect, extremely low risk of micro cracks and increased stability by shingle-tech.
- Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



BSM-SFLEX-110W

Mechanical Data Standard Test Conditions AM=1.5, E=1000W/m2, TC=25°C	
Nominal Power	110W
Cell Type	Monocrystalline
Module	21.1%
Maximum Power Current (Impp)	5.86A
Maximum Power Voltage (Vmpp)	18.80V
Open-circuit Voltage (Voc)	22.30V
Short-circuit Current (Isc)	6.21A
Maximum System Voltage	100V
Output Tolerance	+3%
Cable	900mm / 2.5mm2
Connector Type	MC4 / MC4 Compatible
Module Structure	ETFE / EVA / Backsheet
Junction box rating	≥IP67
Number of Diodes	One
Working Temperature	-20℃~+65℃
Packaging	
Module Dimensions	1160*450*2mm
Module Weight	1.9kg
Package	Single Package
Pieces per Pallet	68
Gross Weight per Pallet	219kg
Pallet Dimensions	1200*1100*1070mm



